

HANDSFREE COLOR VIDEO INTERCOM

JB-Series



Handsfree Communication!

Convenience & Ease-of-Use

Quick and Convenient Handsfree Communication for Door answering and Intercommunication.

JB Handsfree Color Video Entry Security Intercom



In a home environment it seems that you never have enough hands to keep up with the many chores required on a daily basis. Aiphone's JB Series can provide you with a crisp color image and clear audio of your visitor utilizing a "Handsfree" video intercom. If you wish to communicate with the person, momentarily touch the "TALK" buttton once and then begin

talking. You and your visitor can then communicate completely handsfree!

*An optional foot switch or any other dry closure can operate the "TALK" switch externally. *If automatic handsfree communication is not desired, manual TALK/LISTEN operation can be the default setting.



Vandal-Resistant Door Stations



The standard JB door station. Resistant enclosure, choose enclosure, or JB-DVF, flush

Color Visual Identification Day or Night



liahtina conditions. The built-in white LED illuminators, on a low-light



All-Call to all stations

Station-to-Station Communication: Variety of System Configurations



master station, and power additional door station.

The JB Series is available in









Call extension

IER-2



release adaptor



Picture memory unit KC-32FII

RY-3DL Single-gang mounting plate(for JB-DV): MKW-P

SPECIFICATIONS

· Power source: DC 18V

· Consumption: Max. 670mA (JB-2MD), Max. 250mA (JB-2HD) PS-1820UL, PS-1820S, PS-1820DIN, PS-1810DIN(for 1 monitor)

Power supply:

· Calling: Chime. Image & audio approx. 30 sec. Communication: AUTOMATIC (Handsfree): To activate momentarily depress

TALK button, MANUAL (Press-to-talk/Release-to-listen): To

activate, press TALK button for 2 sec. or until talk LED turns on. · Video-monitor: 3-1/2" direct-view TFT color LCD


· Scanning line: 525 lines

· Door release: AC 12V, 0.4A (dry closure contact identified by "L,L" terminals). · Dimensions: 175H x 115W x 43D (mm), 6-7/8"H x 4-7/32"W x 1-11/16"D.

· Weight: JB-2MD 400g (0.9 lbs.) approx.

Handsfree communication is activated by automatic voice switching circuitry, which may cause intermittent audio by the environmental noise level of either inside or outside stations.

UNIT DIMENSIONS



■ WIRING & CABLE

- · Four-wire Monitor-to-Monitor wiring
- · Recommended: Parallel cable or single-sheathed cable. Vinyl-jacket, PE (polyethylene)
- insulation. Never use twisted or shielded pairs, coax. cable or loose wires.
- Distance: ø1.0mm 18AWG

JB-DV/JA-D to Master	100m	330′
Master to Sub	100m	330′
Master to Power Supply	10m	33'
Master to IER-2	150m	500'

Distributed by:











http://www.aiphone.com/

AIPHONE CO. LTD. TOYOTA FACTORY JB-2MD-B(E/A)1203A

Printed in Japan (E)